

**Company:** CHEVRON AMBU  
**Well:** CURRY 8H  
**Field:** FORT BEELER  
**County:** MARSHALL  
**State:** WEST VIRGINIA

**PLATFORM EXPRESS**  
**LITHO-DENSITY / COMPENSATED NEUTRON**  
**GAMMA RAY / CALIPER**

**County:** MARSHALL  
**Field:** FORT BEELER  
**Location:** LAT: 39-54-35.730 N  
**Well:** CURRY 8H  
**Company:** CHEVRON AMBU

Location: LAT: 39-54-35.730 N LONG: 80-39-58.821 W	Elev.: K.B. 1350.10 ft G.L. 1317.00 ft D.F. 1350.10 ft
Permanent Datum: Log Measured From: Drilling Measured From:	Ground Level Kelly Bushing Kelly Bushing
API Serial No. 47-5101784	Section: TOWNSHIP: WASHINGTON
Logging Date 12-Feb-2016	Quad:

Logging Date	12-Feb-2016
Run Number	RUN1A
Depth Driller	11720.00 ft
Schlumberger Depth	11732.00 ft
Bottom Log Interval	11732.00 ft
Top Log Interval	8918.00 ft
Casing Driller Size @ Depth	9.625 in @ 8934.00 ft
Casing Schlumberger	8957 ft
Bit Size	8.5 in
Type Fluid In Hole	Synthetic Oil
Density	12.5 lbm/gal
Fluid Loss	PH
Source of Sample	N/A
RM @ Meas Temp	N/A
RMF @ Meas Temp	N/A
RMG @ Meas Temp	N/A
Source RMF	N/A
RM @ BHT	N/A
RMF @ BHT	N/A
Max Recorded Temperatures	191 degF
Circulation Stopped	Time 12-Feb-2016 04:00:00
Logger on Bottom	Time 12-Feb-2016 18:07:00
Unit Number	2134
Recorded By	BUZZEO
Witnessed By	JUSTIN DEAN

## Disclaimer


THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.


## Contents

- |  |  |
|--|--|
| <ol style="list-style-type: none"> <li>1. Header</li> <li>2. Disclaimer</li> <li>3. Contents</li> <li>4. Well Sketch</li> <li>5. Borehole Size/Casing/Tubing Record</li> <li>6. Remarks and Equipment Summary</li> <li>7. Depth Summary</li> <li>8. Composite 1 MAIN PASS 2"           <ol style="list-style-type: none"> <li>8.1 Integration Summary</li> <li>8.2 Software Version</li> <li>8.3 Composite Summary</li> <li>8.4 Log ( RANGE PEX NUC 2IN )</li> <li>8.5 Parameter Listing</li> </ol> </li> <li>9. Composite 1 MAIN PASS 5"           <ol style="list-style-type: none"> <li>9.1 Integration Summary</li> <li>9.2 Software Version</li> <li>9.3 Composite Summary</li> </ol> </li> </ol> | <ol style="list-style-type: none"> <li>10.5 Parameter Listing</li> <li>11. RUN1A HiRes REPEAT PASS           <ol style="list-style-type: none"> <li>11.1 Integration Summary</li> <li>11.2 Software Version</li> <li>11.3 Composite Summary</li> <li>11.4 Log ( HIRES NUC 5IN )</li> <li>11.5 Parameter Listing</li> </ol> </li> <li>12. Calibration Report</li> <li>13. Tail</li> </ol> |
|--|--|

- 9.4 Log ( RANGE PEX NUC 5IN )
- 9.5 Parameter Listing
- 10. RUN1A REPEAT PASS 5"
- 10.1 Integration Summary
- 10.2 Software Version
- 10.3 Composite Summary
- 10.4 Log ( RANGE PEX NUC 5IN )

## Well Sketch





### Borehole Size/Casing/Tubing Record

Bit						
Bit Size ( in )	8.5					
Top Driller ( ft )	0					
Top Logger ( ft )	0					
Bottom Driller ( ft )	11720					
Bottom Logger ( ft )	11732					
Casing						
Size ( in )	9.625					
Weight ( lbm/ft )	40					
Inner Diameter ( in )	8.835					
Grade	N/A					
Top Driller ( ft )	0					
Top Logger ( ft )	0					
Bottom Driller ( ft )	8934					
Bottom Logger ( ft )	8957					

### Remarks and Equipment Summary

RUN1A: Toolstring				RUN1A: Remarks	
<b>Equip name</b> LEH-MT LEH-MT	<b>Length</b> 117.62	<b>MP name</b>	<b>Offset</b>	THANK YOU FOR CHOOSING SCHLUMBERGER!	
		<b>Mud Temperature</b>	115.68	ALL LOGGING INTERVALS AS PER CLIENT REQUEST	
<b>EDTC-B:800 1</b> EDTH-B:8001 EDTG-A:7724 4 EDTC-B:8001	114.47			LIMITED MUD PROPERTIES AVAILABLE. LOGGED IN OIL BASED MUD.	
		<b>CTEM</b>	110.97	TOOLS RAN AS PER TOOL SKETCH	
		<b>ACCZ</b>	0.00	FORMATION AND WELL PROPERTIES AS PER CLIENT REQUEST	
		<b>HV</b>	0.00	ALL HEADER INFORMATION PROVIDED CLIENT	
		<b>Gamma Ray</b>	109.1	RIG: NABORS X07	
		<b>TelStatus</b>	107.97	LIMESTONE MATRIX USED. DENSITY OF 2.68 USED.	
<b>PPC-B[2]:87 32</b> PPC-B:8732	107.97			BARITE CORRECTION APPLIED.	
		<b>PPC-B Calipers</b>	106.82	PER CLIENT SOP, CALIPERS CLOSED BEFORE CASING.	



MAST-B:857 101.45

7

ECH-SF:8381

MAPC-BA:839

4

MAMS-CA:85

77

MASS-BA:815

5

MAXS-BA:835


5

MAMS

86.01

<b>PPC-B[1]:8227</b>	<b>60.17</b>		<b>MAXS</b>	<b>60.17</b>
			<b>PPC-B Calipers</b>	<b>59.02</b>
<b>Adaptor_Head[2]</b>	<b>53.65</b>	1793		
<b>GPIT-F:1875</b>	<b>49.65</b>		<b>GPIT-F Inc linometer</b>	<b>48.23</b>
GPIT-B:3703 GPIC-F:1875 DHRU-F:1981			<b>GPIT</b>	<b>0.00</b>
<b>Adaptor_Head[1]</b>	<b>45.65</b>	1764		
<b>AH-107[2]</b>	<b>41.65</b>	3978		
<b>AH-107[1]</b>	<b>39.65</b>	3975		
<b>HGNS-H:4887</b>	<b>37.65</b>		<b>Temperature</b>	<b>37.62</b>
HGNH:4712 NPV-N NSR-F:5159 HACCZ-H:7079 HGNS-H:4887 HMCA-H			<b>GR</b>	<b>36.91</b>
			<b>CNL Porosity</b>	<b>30.57</b>
			<b>HGNS</b>	<b>28.24</b>
			<b>HMCA</b>	<b>28.24</b>
			<b>Accelerometer</b>	<b>0.00</b>
<b>HDRS-H:8606</b>	<b>28.24</b>			
ECH-MEB:4916 HRCC-H:4769 HRMS-H:860 GSR-J:5541 Backscatter:41150 Short Spacing:42161 HRGD-H:4901 Long Spacing:43095 GPV-Q			<b>HRCC</b>	<b>24.24</b>

AIT-M:275 16.00  
 AMIS:275  
 AMRM:275



Lengths are in ft

Maximum Outer Diameter = 9.000 in

Line: Sensor Location, Value: Gating Offset

All measurements are relative to TOOL\_ZERO

## Depth Summary

RUN1A

### Depth Measuring Device

Type	IDW-JA
Serial Number	6442
Calibration Date	12-JAN-2016
Calibrator Serial Number	
Calibration Cable Type	7-46 AXS
Wheel Correction 1	-7
Wheel Correction 2	-5

### Tension Device

Type	CMTD-B/A
Serial Number	2016
Calibration Date	03-FEB-2016
Calibrator Serial Number	78796A
Number of Calibration Points	10
Calibration Root Mean Square Error	53
Calibration Peak Error	82

### Logging Cable

Type	7-46A-XS		
Serial Number	U715044		
Length	22840.00 ft		
Conveyance Type	Wireline		
Rig Type	LAND		

<b>RUN1A:Depth Control Parameters</b>		<b>Depth Control Remarks</b>
Log Sequence	First Log In the Well	ALL SCHLUMBERGER FIRST RUN IN HOLE PROCEDURES FOLLOWED.
Rig Up Length At Surface		IDW USED AS PRIMARY DEPTH CONTROL
Rig Up Length At Bottom		ZCHART USED AS SECONDARY CONTROL
Rig Up Length Correction		EDTC GAMMA RAY FROM LOG DOWN USED TO PUT ON DEPTH.
Stretch Correction	10.00 ft	
Tool Zero Check At Surface		

### Composite 1

### MAIN PASS 2"

#### Integration Summary

Output Channel(s)	Output Description	Input Parameter	Output Value	Unit
IHV	Integrated Hole Volume	GCSE_UP_PASS, GCSE_DOWN_PASS:RUN1A	989.81	ft3
ICV	Integrated Cement Volume	GCSE_UP_PASS, GCSE_DOWN_PASS:RUN1A, FCD	537.95	ft3

#### Software Version

<b>Acquisition System</b>	<b>Version</b>
Maxwell 2016 SP1	6.1.58882.3100

#### Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
RUN1A	Log[8]:Up	Up	9046.84 ft	11748.05 ft	12-Feb-2016 6:58:23 PM	12-Feb-2016 9:08:29 PM	ON	10.70 ft	No
RUN1A	Log[9]:Up	Up	8449.75 ft	9312.09 ft	12-Feb-2016 9:24:58 PM	12-Feb-2016 9:40:25 PM	ON	9.92 ft	No
RUN1A	Log[11]:Up	Up	209.49 ft	8689.33 ft	12-Feb-2016 10:01:48 PM	12-Feb-2016 11:46:31 PM	ON	9.66 ft	No

All depths are referenced to toolstring zero

#### Log

Company:CHEVRON AMBU    Well:CURRY 8H  
Composite 1:S004

Description: Triple Combo standard resolution template for Platform Express    Format: Log ( RANGE PEX NUC 2IN )    Index Scale: 2 in per 100 ft    Index Unit: ft    Index Type: Measured Depth    Creation Date: 13-Feb-2016 01:44:35

Channel	Source	Sampling
BS	Borehole	6in
CALI	HDRS[1]:HRCC-H[1]:HRCC-H[1]	1in
DPH8	HDRS[1]:HRMS-H[1]:HRGD-H[1]	2in
GR	EDTC-B[1]:EDTC-B[1]:EDTC-B[1]	6in
HDRS	HDRS[1]:HRMS-H[1]:HRGD-H[1]	2in
ICV	Borehole	6in
IHV	Borehole	6in
NPHI	HGNS[1]:HGNS-H[1]:HGNS-H[1]	6in
PEF8	HDRS[1]:HRMS-H[1]:HRGD-H[1]	2in
RHO8	HDRS[1]:HRMS-H[1]:HRGD-H[1]	2in
TENS	WLWorkflow	6in

IHV - Integrated Hole Volume every 100.00 (ft3)

ICV - Integrated Cement Volume every 10.00 (ft3)

TIME\_1900 - Time Marked every 60.00 (s)

IHV - Integrated Hole Volume every 10.00 (ft3)

GR > 200 GAPI

GR > 400 GAPI

Caliper (HCAL) HDRS[1]  
6 in 16

Cable Tension (TENS)  
6000 lbf 0

Bit Size (BS)  
6 in 16

Gamma Ray (ECGR\_EDTC) EDTC-B[1]  
0 gAPI 200

Density Standoff Correction (HDRA) HDRS[1]  
-0.05 g/cm3 0.45


GAS EFFECT

Thermal Neutron Porosity (original Ratio Method) in Selected Lithology (NPHI) HGNS[1]  
0.3 ft3/ft3 -0.1



High Resolution Density Porosity (DPH8) HDRS[1]  
0.45 ft3/ft3 -0.15

High Resolution Formation Photoelectric Factor (PEF8) HDRS[1]  
0 10



High Resolution Formation Density (RHO8) HDRS[1]  
2 g/cm3 3









1000  
1050  
1100  
1150  
1200  
1250  
1300  
1350  
1400  
1450  
1500





2100

2150

2200

2250

2300

2350

2400

2450

2500


2550

2600



ECGR EDTC



TENS

NPHI




2650  
2700  
2750  
2800  
2850  
2900  
2950  
3000  
3050  
3100  
3150






3750  
3800  
3850  
3900  
3950  
4000  
4050  
4100  
4150  
4200  
4250





EGR ETC

TENS




NPHT






4850  
4900  
4950  
5000  
5050  
5100  
5150  
5200  
5250  
5300  
5350







CGREDTC



TENS





HPM















7050  
7100  
7150  
7200  
7250  
7300  
7350  
7400  
7450  
7500  
7550











9250  
9300  
9350  
9400  
9450  
9500  
9550  
9600  
9650  
9700  
9750

ECGR\_EDTC

BS

TENS

HCAL



PHF8


HDRA



NPT


PH08

DPH8









GR > 200 GAPI		
GR > 400 GAPI		
Caliper (HCAL) HDRS[1]		
6	in	16
Cable Tension (TENS)		
6000	lbf	0
Bit Size (BS)		
6	in	16
Gamma Ray (ECGR_EDTC) EDTC-B[1]		
0	gAPI	200

GAS EFFECT		
Thermal Neutron Porosity (original Ratio Method) in Selected Lithology (NPHI) HGNS[1]		
0.3	ft3/ft3	-0.1
High Resolution Density Porosity (DPH8) HDRS[1]		
0.45	ft3/ft3	-0.15
High Resolution Formation Photoelectric Factor (PEF8) HDRS[1]		
0		10
High Resolution Formation Density (RHO8) HDRS[1]		
2	g/cm3	3
Density Standoff Correction (HDRA) HDRS[1]		
-0.05	g/cm3	0.45

- IHV - Integrated Hole Volume every 10.00 (ft3)
- TIME\_1900 - Time Marked every 60.00 (s)
- ICV - Integrated Cement Volume every 10.00 (ft3)
- IHV - Integrated Hole Volume every 100.00 (ft3)

Description: Triple Combo standard resolution template for Platform Express    Format: Log ( RANGE PEX NUC 2IN )    Index Scale: 2 in per 100 ft    Index Unit: ft    Index Type: Measured Depth    Creation Date: 13-Feb-2016 01:44:35

Channel Processing Parameters				
RUN1A: Parameters				
Parameter	Description	Tool	Value	Unit

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	Yes	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Open	
BS	Bit Size	WLSESSION	8.5	in
CALI_SHIFT	CALI Supplementary Offset	HDRS-H	0	in
CBLO	Casing Bottom (Logger)	WLSESSION	8957	ft
CDEN	Cement Density	EDTC-B	2	g/cm3
CSODDRL	Casing Outer Diameter - Zoned along driller depths	WLSESSION	9.625	in
DC_MODE	Depth Correction Mode	DepthCorrection	Real-time	
DFD	Drilling Fluid Density	Borehole	12.5	lbm/gal
DFT	Drilling Fluid Type	Borehole	Oil	
DHC	Density Hole Correction	HDRS-H	Bit Size	
FCD	Future Casing (Outer) Diameter	WLSESSION	5.5	in
FD	Fluid Density	Borehole	1	g/cm3
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	CALI	
MATR	Rock Matrix for Neutron Porosity Corrections	Borehole	LIMESTONE	
MDEN	Matrix Density for Density Porosity	Borehole	2.68	g/cm3
NPRM	HRDD Nuclear Processing Mode	HDRS-H	Time Zoned	
TPOS_EDTC	Tool Position: Centered or Eccentered	EDTC-B	Centered	

### RUN1A Time Zoned Parameters

#### Pass Log[8]:Up

Parameter	Value	Start Time	Stop Time	Start Depth ( ft )	Stop Depth ( ft )
NPRM	High Resolution	12-Feb-2016 18:58:34	12-Feb-2016 21:08:29	11747.6	9050.39

#### Pass Log[9]:Up

NPRM	High Resolution	12-Feb-2016 21:28:52	12-Feb-2016 21:40:25	9088.93	8489.94
------	-----------------	----------------------	----------------------	---------	---------

All depth are at tool zero.

### Tool Control Parameters

#### RUN1A: Parameters

Parameter	Description	Tool	Value	Unit
HRGD_BOARD_TYPE	HRGD Board Type	HDRS-H	WITH_HET	
MAX_LOG_SPEED	Toolstring Maximum Logging Speed	WLSESSION	Time Zoned	ft/h

### RUN1A Time Zoned Parameters

#### Pass Log[8]:Up

Parameter	Value	Start Time	Stop Time	Start Depth ( ft )	Stop Depth ( ft )
MAX_LOG_SPEED	1443	12-Feb-2016 18:58:23	12-Feb-2016 19:13:31	11747.6	11461.7
MAX_LOG_SPEED	1528	12-Feb-2016 19:13:31	12-Feb-2016 20:48:03	11461.7	9385.71
MAX_LOG_SPEED	1425	12-Feb-2016 20:48:03	12-Feb-2016 20:57:18	9385.71	9192.53
MAX_LOG_SPEED	1516	12-Feb-2016 20:57:18	12-Feb-2016 21:08:29	9192.53	9050.39

#### Pass Log[9]:Up

MAX_LOG_SPEED	1516	12-Feb-2016 21:28:52	12-Feb-2016 21:40:25	9088.93	8489.94
---------------	------	----------------------	----------------------	---------	---------

#### Pass Log[11]:Up

MAX_LOG_SPEED	1516	12-Feb-2016 22:04:56	12-Feb-2016 23:46:31	8509.74	209.6
---------------	------	----------------------	----------------------	---------	-------

All depth are at tool zero.

## Composite 1

# MAIN PASS 5"

## Integration Summary

Output Channel(s)	Output Description	Input Parameter	Output Value	Unit
IHV	Integrated Hole Volume	GCSE_UP_PASS, GCSE_DOWN_PASS:RUN1A	989.81	ft3
ICV	Integrated Cement Volume	GCSE_UP_PASS, GCSE_DOWN_PASS:RUN1A, FCD	537.95	ft3

## Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

## Composite Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
RUN1A	Log[8]:Up	Up	9046.84 ft	11748.05 ft	12-Feb-2016 6:58:23 PM	12-Feb-2016 9:08:29 PM	ON	10.70 ft	No
RUN1A	Log[9]:Up	Up	8449.75 ft	9312.09 ft	12-Feb-2016 9:24:58 PM	12-Feb-2016 9:40:25 PM	ON	9.92 ft	No
RUN1A	Log[11]:Up	Up	209.49 ft	8689.33 ft	12-Feb-2016 10:01:48 PM	12-Feb-2016 11:46:31 PM	ON	9.66 ft	No

All depths are referenced to toolstring zero

## Log

Company:CHEVRON AMBU    Well:CURRY 8H  
Composite 1:S004

Description: Triple Combo standard resolution template for Platform Express    Format: Log ( RANGE PEX NUC 5IN )    Index Scale: 5 in per 100 ft    Index Unit: ft    Index Type: Measured Depth    Creation Date: 13-Feb-2016 01:44:40

Channel	Source	Sampling
BS	Borehole	6in
CALI	HDRS[1]:HRCC-H[1]:HRCC-H[1]	1in
DPHZ	HDRS[1]:HRMS-H[1]:HRGD-H[1]	2in
GR	EDTC-B[1]:EDTC-B[1]:EDTC-B[1]	6in
HDRA	HDRS[1]:HRMS-H[1]:HRGD-H[1]	2in
ICV	Borehole	6in
IHV	Borehole	6in
NPHI	HGNS[1]:HGNS-H[1]:HGNS-H[1]	6in
PEFZ	HDRS[1]:HRMS-H[1]:HRGD-H[1]	2in
RHOZ	HDRS[1]:HRMS-H[1]:HRGD-H[1]	2in
TENS	WLWorkflow	6in
TIME_1900	WLWorkflow	0.1in

— IHV - Integrated Hole Volume every 100.00 (ft3)

— ICV - Integrated Cement Volume every 10.00 (ft3)

— IHV - Integrated Hole Volume every 10.00 (ft3)

TIME\_1900 - Time Marked every 60.00 (s)

GR > 200 GAPI
GR > 400 GAPI
Caliper (HCAL) HDRS[1]
6                      in                      16
Cable Tension (TENS)
8000                      lbf                      0
Bit Size (BS)

Density Standoff Correction (HDRA) HDRS[1]

-0.05                      g/cm3                      0.45

GAS EFFECT

Standard Resolution Formation Density (RHOZ) HDRS[1]


2                                      g/cm3                                      3

Standard Resolution Density Porosity (DPHZ) HDRS[1]


0.3                                      ft3/ft3                                      -0.1

Thermal Neutron Porosity (original Ratio Method) in Selected Lithology (NPHI) HGNS[1]



Gamma Ray (ECGR\_EDTC) EDTC-B[1]







Standard Resolution Formation Photoelectric Factor (PEFZ) HDRS[1]
























1190  
1200  
1210  
1220  
1230  
1240  
1250  
1260  
1270  
1280  
1290  
1300  
1310  
1320  
1330  
1340  
1350  
1360  
1370  
1380  
1390  
1400























2290  
2300  
2310  
2320  
2330  
2340  
2350  
2360  
2370  
2380  
2390  
2400  
2410  
2420  
2430  
2440  
2450  
2460  
2470  
2480  
2490  
2500



NPHI





2950

2960

2970

2980

2990

3000

3010

3020

3030

3040

3050

3060

3070

3080

3090

3100

3110

3120

3130

3140


3150



3160

ECGR EBTC



TENS



NPH









NPHI



























EGGR EDTC

TENS

NPHT

5150

5160

5170

5180

5190

5200

5210

5220

5230

5240

5250

5260

5270

5280

5290

5300

5310

5320

5330

5340


5350



5360

ECCR EDTC



TENS

NPHI














EGGR\_EDTC



TENS



NPFI































7570  
7580  
7590  
7600  
7610  
7620  
7630  
7640  
7650  
7660  
7670  
7680  
7690  
7700  
7710  
7720  
7730  
7740  
7750  
7760  
7770  
7780











8230  
8240  
8250  
8260  
8270  
8280  
8290  
8300  
8310  
8320  
8330  
8340  
8350  
8360  
8370  
8380  
8390  
8400  
8410  
8420  
8430  
8440




EGGR EDTC

TENS

NPHI





8450  
8460  
8470  
8480  
8490  
8500  
8510  
8520  
8530  
8540  
8550  
8560  
8570  
8580  
8590  
8600  
8610  
8620  
8630  
8640  
8650  
8660




ECCR EDTG



TENS


NPHI















































GR > 200 GAPI		
GR > 400 GAPI		
Caliper (HCAL) HDRS[1]		
6	in	16
Cable Tension (TENS)		
8000	lbf	0
Bit Size (BS)		
6	in	16
Gamma Ray (ECGR_EDTC) EDTC-B[1]		
0	gAPI	200

GAS EFFECT		
Standard Resolution Formation Density (RHOZ) HDRS[1]		
2	g/cm3	3
Standard Resolution Density Porosity (DPHZ) HDRS[1]		
0.3	ft3/ft3	-0.1
Thermal Neutron Porosity (original Ratio Method) in Selected Lithology (NPHI) HGNS[1]		
0.3	ft3/ft3	-0.1
Standard Resolution Formation Photoelectric Factor (PEFZ) HDRS[1]		
0		10
Density Standoff Correction (HDRA) HDRS[1]		
-0.05	g/cm3	0.45

TIME\_1900 - Time Marked every 60.00 (s)

— IHV - Integrated Hole Volume every 10.00 (ft3)

— ICV - Integrated Cement Volume every 10.00 (ft3)

— IHV - Integrated Hole Volume every 100.00 (ft3)

Description: Triple Combo standard resolution template for Platform Express Format: Log ( RANGE PEX NUC 5IN ) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 13-Feb-2016 01:44:40

## Channel Processing Parameters

### RUN1A: Parameters

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	Yes	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Open	
BS	Bit Size	WLSESSION	8.5	in
CALI_SHIFT	CALI Supplementary Offset	HDRS-H	0	in
CBLO	Casing Bottom (Logger)	WLSESSION	8957	ft
CDEN	Cement Density	EDTC-B	2	g/cm3
CSODDRL	Casing Outer Diameter - Zoned along driller depths	WLSESSION	9.625	in
DC_MODE	Depth Correction Mode	DepthCorrection	Real-time	
DFD	Drilling Fluid Density	Borehole	12.5	lbm/gal
DFT	Drilling Fluid Type	Borehole	Oil	
DHC	Density Hole Correction	HDRS-H	Bit Size	
FCD	Future Casing (Outer) Diameter	WLSESSION	5.5	in
FD	Fluid Density	Borehole	1	g/cm3
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	CALI	
MATR	Rock Matrix for Neutron Porosity Corrections	Borehole	LIMESTONE	
MDEN	Matrix Density for Density Porosity	Borehole	2.68	g/cm3
NPRM	HRDD Nuclear Processing Mode	HDRS-H	Time Zoned	
TPOS_EDTC	Tool Position: Centered or Eccentered	EDTC-B	Centered	

### RUN1A Time Zoned Parameters

#### Pass Log[8]:Up

Parameter	Value	Start Time	Stop Time	Start Depth ( ft )	Stop Depth ( ft )
NPRM	High Resolution	12-Feb-2016 18:58:34	12-Feb-2016 21:08:29	11747.6	9050.39

#### Pass Log[9]:Up

NPRM	High Resolution	12-Feb-2016 21:28:52	12-Feb-2016 21:40:25	9088.93	8489.94
------	-----------------	----------------------	----------------------	---------	---------

All depth are at tool zero.

## Tool Control Parameters

### RUN1A: Parameters

Parameter	Description	Tool	Value	Unit
HRGD_BOARD_TYPE	HRGD Board Type	HDRS-H	WITH_HET	
MAX_LOG_SPEED	Toolstring Maximum Logging Speed	WLSESSION	Time Zoned	ft/h

### RUN1A Time Zoned Parameters

#### Pass Log[8]:Up

Parameter	Value	Start Time	Stop Time	Start Depth ( ft )	Stop Depth ( ft )
MAX_LOG_SPEED	1443	12-Feb-2016 18:58:23	12-Feb-2016 19:13:31	11747.6	11461.7
MAX_LOG_SPEED	1528	12-Feb-2016 19:13:31	12-Feb-2016 20:48:03	11461.7	9385.71
MAX_LOG_SPEED	1425	12-Feb-2016 20:48:03	12-Feb-2016 20:57:18	9385.71	9192.53
MAX_LOG_SPEED	1516	12-Feb-2016 20:57:18	12-Feb-2016 21:08:29	9192.53	9050.39

#### Pass Log[9]:Up

MAX_LOG_SPEED	1516	12-Feb-2016 21:28:52	12-Feb-2016 21:40:25	9088.93	8489.94
---------------	------	----------------------	----------------------	---------	---------

#### Pass Log[11]:Up

MAX_LOG_SPEED	1516	12-Feb-2016 22:04:56	12-Feb-2016 23:46:31	8509.74	209.6
---------------	------	----------------------	----------------------	---------	-------

All depth are at tool zero.

## RUN1A

### REPEAT PASS 5"

### Integration Summary

Output Channel(s)	Output Description	Input Parameter	Output Value	Unit
IHV	Integrated Hole Volume	GCSE_UP_PASS	231.18	ft3
ICV	Integrated Cement Volume	GCSE_UP_PASS, FCD	127.13	ft3

### Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

### Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
RUN1A	Repeat[5]:Up	Up	11101.15 ft	11751.78 ft	12-Feb-2016 6:07:36 PM	12-Feb-2016 6:40:53 PM	ON	9.91 ft	No

All depths are referenced to toolstring zero

### Log

Company:CHEVRON AMBU Well:CURRY 8H

RUN1A: Repeat[5]:Up:S004






Description: Triple Combo standard resolution template for Platform Express Format: Log ( RANGE PEX NUC 5IN ) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 13-Feb-2016 01:44:45


Channel	Source	Sampling
BS	Borehole	6in
CALI	HDRS-H:HRCC-H:HRCC-H	1in
DPHZ	HDRS-H:HRMS-H:HRGD-H	2in
GR	EDTC-B:EDTC-B:EDTC-B	6in
HDRA	HDRS-H:HRMS-H:HRGD-H	2in
ICV	Borehole	6in
IHV	Borehole	6in
NPHI	HGNS-H:HGNS-H:HGNS-H	6in

PEFZ HDRS-H:HRMS-H:HRGD-H 2in  
 RHOZ HDRS-H:HRMS-H:HRGD-H 2in  
 TENS WLWorkflow 6in  
 TIME\_1900 WLWorkflow 0.1in


— IHV - Integrated Hole Volume every 100.00 (ft3)  
 — ICV - Integrated Cement Volume every 10.00 (ft3)  
 — IHV - Integrated Hole Volume every 10.00 (ft3)


TIME\_1900 - Time Marked every 60.00 (s)











GR > 200 GAPI		
GR > 400 GAPI		
Caliper (HCAL) HDRS-H		
6	in	16
Cable Tension (TENS)		
8000	lbf	0
Bit Size (BS)		
6	in	16
Gamma Ray (ECGR_EDTC) EDTC-B		
0	gAPI	200

GAS EFFECT		
Standard Resolution Formation Density (RHOZ) HDRS-H		
2	g/cm3	3
Standard Resolution Density Porosity (DPHZ) HDRS-H		
0.3	ft3/ft3	-0.1
Thermal Neutron Porosity (original Ratio Method) in Selected Lithology (NPHI) HGNS-H		
0.3	ft3/ft3	-0.1
Standard Resolution Formation Photoelectric Factor (PEFZ) HDRS-H		
0		10
Density Standoff Correction (HDRA) HDRS-H		
-0.05	g/cm3	0.45

TIME\_1900 - Time Marked every 60.00 (s)

- | IHV - Integrated Hole Volume every 10.00 (ft3)
- | ICV - Integrated Cement Volume every 10.00 (ft3)
- | IHV - Integrated Hole Volume every 100.00 (ft3)

Description: Triple Combo standard resolution template for Platform Express Format: Log ( RANGE PEX NUC 5IN ) Index Scale: 5 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 13-Feb-2016 01:44:45

## Channel Processing Parameters

### RUN1A: Parameters

Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	Yes	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Open	
BS	Bit Size	WLSESSION	8.5	in
CALI_SHIFT	CALI Supplementary Offset	HDRS-H	0	in
CBLO	Casing Bottom (Logger)	WLSESSION	8957	ft
CDEN	Cement Density	EDTC-B	2	g/cm3
DC_MODE	Depth Correction Mode	DepthCorrection	Real-time	
DFD	Drilling Fluid Density	Borehole	12.5	lbm/gal
DFT	Drilling Fluid Type	Borehole	Oil	
DHC	Density Hole Correction	HDRS-H	Bit Size	
FCD	Future Casing (Outer) Diameter	WLSESSION	5.5	in
FD	Fluid Density	Borehole	1	g/cm3

GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	CALI	
MATR	Rock Matrix for Neutron Porosity Corrections	Borehole	LIMESTONE	
MDEN	Matrix Density for Density Porosity	Borehole	2.68	g/cm3
NPRM	HRDD Nuclear Processing Mode	HDRS-H	High Resolution	
TPOS_EDTC	Tool Position: Centered or Eccentered	EDTC-B	Centered	

## Tool Control Parameters

### RUN1A: Parameters

Parameter	Description	Tool	Value	Unit
HRGD_BOARD_TYPE	HRGD Board Type	HDRS-H	WITH_HET	
MAX_LOG_SPEED	Toolstring Maximum Logging Speed	WLSESSION	Time Zoned	ft/h

### Time Zone Parameters

Parameter	Value	Start Time	Stop Time	Start Depth ( ft )	Stop Depth ( ft )
MAX_LOG_SPEED	1426	12-Feb-2016 18:07:36	12-Feb-2016 18:24:14	11751.78	11456.92
MAX_LOG_SPEED	1510	12-Feb-2016 18:24:14	12-Feb-2016 18:40:53	11456.92	11101.15

All depth are at tool zero.

## RUN1A

### HiRes REPEAT PASS

### Integration Summary

Output Channel(s)	Output Description	Input Parameter	Output Value	Unit
IHV	Integrated Hole Volume	GCSE_UP_PASS	231.18	ft3
ICV	Integrated Cement Volume	GCSE_UP_PASS, FCD	127.13	ft3

### Software Version

Acquisition System	Version
Maxwell 2016 SP1	6.1.58882.3100

### Pass Summary

Run Name	Pass Objective	Direction	Top	Bottom	Start	Stop	DSC Mode	Depth Shift	Include Parallel Data
RUN1A	Repeat[5]:Up	Up	11101.15 ft	11751.78 ft	12-Feb-2016 6:07:36 PM	12-Feb-2016 6:40:53 PM	ON	9.91 ft	No

All depths are referenced to toolstring zero

## Log

Company:CHEVRON AMBU Well:CURRY 8H

RUN1A: Repeat[5]:Up:S004

Description: Triple Combo standard resolution template for Platform Express Format: Log ( HIRES NUC 5IN ) Index Scale: 10 in per 100 ft Index Unit: ft  
Index Type: Measured Depth Creation Date: 13-Feb-2016 01:44:48

Channel	Source	Sampling
BS	Borehole	6in
CALI	HDRS-H:HRCC-H:HRCC-H	1in
DPH8	HDRS-H:HRMS-H:HRGD-H	2in
GR	EDTC-B:EDTC-B:EDTC-B	6in
HDRA	HDRS-H:HRMS-H:HRGD-H	2in
ICV	Borehole	6in
IHV	Borehole	6in
NPOR	HGNS-H:HGNS-H:HGNS-H	6in
PEF8	HDRS-H:HRMS-H:HRGD-H	2in
RHO8	HDRS-H:HRMS-H:HRGD-H	2in
TENS	WLWorkflow	6in

IHV - Integrated Hole Volume every 100.00 (ft3)  
ICV - Integrated Cement Volume every 10.00 (ft3)  
IHV - Integrated Hole Volume every 10.00 (ft3)

TIME\_1900 - Time Marked every 60.00 (s)

**GR > 200 GAPI**

**GR > 400 GAPI**

Caliper (HCAL) HDRS-H  
10 in 20

Cable Tension (TENS)  
6000 lbf 0

Gamma Ray (ECGR\_EDTC) EDTC-B  
0 gAPI 200

Bit Size (BS)  
6 in 16

Density Standoff Correction (HDRA) HDRS-H  
-0.05 g/cm3 0.45



**GAS EFFECT**



High Resolution Formation Density (RHO8) HDRS-H  
2 g/cm3 3



High Resolution Formation Photoelectric Factor (PEF8) HDRS-H  
0 10



High Resolution Density Porosity (DPH8) HDRS-H  
0.3 ft3/ft3 -0.1



Enhanced Thermal Neutron Porosity in Selected Lithology (NPOR) HGNS-H  
0.3 ft3/ft3 -0.1




















TIME\_1900 - Time Marked every 60.00 (s)

- IHV - Integrated Hole Volume every 10.00 (ft3)
- ICV - Integrated Cement Volume every 10.00 (ft3)
- IHV - Integrated Hole Volume every 100.00 (ft3)

Description: Triple Combo standard resolution template for Platform Express Format: Log ( HIRES NUC 5IN ) Index Scale: 10 in per 100 ft Index Unit: ft  
 Index Type: Measured Depth Creation Date: 13-Feb-2016 01:44:48

## Channel Processing Parameters

RUN1A: Parameters				
Parameter	Description	Tool	Value	Unit
ISSBAR	Barite Mud Presence Flag	Borehole	Yes	
BHS	Borehole Status (Open or Cased Hole)	Borehole	Open	
BHT	Bottom Hole Temperature	Borehole	191	degF
BS	Bit Size	WLSESSION	8.5	in
BSAL	Borehole Salinity	Borehole	0	ppm
CALI_SHIFT	CALI Supplementary Offset	HDRS-H	0	in
CBLO	Casing Bottom (Logger)	WLSESSION	8957	ft
CDEN	Cement Density	EDTC-B	2	g/cm3
DC_MODE	Depth Correction Mode	DepthCorrection	Real-time	
DFD	Drilling Fluid Density	Borehole	12.5	lbm/gal
DFT	Drilling Fluid Type	Borehole	Oil	
DHC	Density Hole Correction	HDRS-H	Bit Size	
FCD	Future Casing (Outer) Diameter	WLSESSION	5.5	in
FD	Fluid Density	Borehole	1	g/cm3
FSAL	Formation Salinity	Borehole	0	ppm
GCSE_DOWN_PASS	Generalized Caliper Selection for WL Log Down Passes	Borehole	BS	
GCSE_UP_PASS	Generalized Caliper Selection for WL Log Up Passes	Borehole	CALI	
GRSE	Generalized Mud Resistivity Selection, from Measured or Computed Mud Resistivity	Borehole	AMF	
GTSE	Generalized Temperature Selection, from Measured or Computed Temperature	Borehole	CTEM	
HSCO	Hole Size Correction Option	HGNS-H	Yes	

MATR	Rock Matrix for Neutron Porosity Corrections	Borehole	LIMESTONE	
MDEN	Matrix Density for Density Porosity	Borehole	2.68	g/cm3
NPRM	HRDD Nuclear Processing Mode	HDRS-H	High Resolution	
SOCO	Standoff Correction Option	HGNS-H	Yes	
TPOS_EDTC	Tool Position: Centered or Eccentered	EDTC-B	Centered	

## Tool Control Parameters

### RUN1A: Parameters

Parameter	Description	Tool	Value	Unit
HMCA_BOARD_TYPE	HMCA Board Type	HGNS-H	1	
HRGD_BOARD_TYPE	HRGD Board Type	HDRS-H	WITH_HET	
MAX_LOG_SPEED	Toolstring Maximum Logging Speed	WLSESSION	Time Zoned	ft/h

### Time Zone Parameters

Parameter	Value	Start Time	Stop Time	Start Depth ( ft )	Stop Depth ( ft )
MAX_LOG_SPEED	1426	12-Feb-2016 18:07:36	12-Feb-2016 18:24:14	11751.78	11456.92
MAX_LOG_SPEED	1510	12-Feb-2016 18:24:14	12-Feb-2016 18:40:53	11456.92	11101.15

All depth are at tool zero.

## Calibration Report

### HDRS-H (HILT Density and Rxo Sonde, 150 degC) Calibration - Run RUN1A

#### Primary Equipment :

HILT High-Resolution Control Cartridge, 150 degC	HRCC-H	4769
HILT Resistivity Gamma-Ray Density Device, 150 degC	HRGD-H	4901

#### Auxiliary Equipment :

HRDD Backscatter Detector	Backscatter	41150
HRDD Long Spacing Detector	Long Spacing	43095
HRDD Short Spacing Detector	Short Spacing	42161
Cesium 137 Gamma-Ray Logging Source	GSR-J	5541
HILT High-Resolution Control Cartridge, 150 degC	HRCC-H	4769
HILT High-Resolution Mechanical Sonde, 150 degC	HRMS-H	860

#### Calibration Parameter :

Small Ring Size (Caliper Calibration Small Ring)	8.00
Large Ring Size (Caliper Calibration Large Ring)	12.00

### HDRS Caliper Calibration - Caliper Accumulations

Before (Measured): **13:26:09 04-Feb-2016** Expired by 7 days

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Small Ring	in	Before	8.00	6.00	7.91	10.00	
Large Ring	in	Before	12.00	9.00	12.20	15.00	

### HDRS Density Calibration - Inversion Results

Master (EEPROM): 14:12:16 01-Feb-2016

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Rho Aluminum	g/cm3	Master	2.596	2.586	2.592	2.606	
Rho Magnesium	g/cm3	Master	1.686	1.676	1.689	1.696	
Pe Aluminum		Master	2.570	2.470	2.510	2.670	
Pe Magnesium		Master	2.650	2.550	2.639	2.750	

### HDRS Density Calibration - Deviation Summary

Master (EEPROM): 14:12:16 01-Feb-2016

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
BS Average Deviation	%	Master	0	-0.6000	0.2445	0.6000	
BS Max Deviation	%	Master	0	-1.6000	0.5918	1.6000	
SS Average Deviation	%	Master	0	-1.0000	0.7086	1.0000	
SS Max Deviation	%	Master	0	-2.5000	1.4504	2.5000	

LS Average Deviation	%	Master	0	-1.5000	1.3918	1.5000	
LS Max Deviation	%	Master	0	-3.5000	3.3688	3.5000	

### HDRS Density Calibration - Background Summary

Master (EEPROM):		14:12:16 01-Feb-2016		Before (Measured):		13:28:55 04-Feb-2016 Expired by 7 days	
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
BS Window Ratio		Master	1.0000		0.7503		
		Before	0.7503	0.7128	0.7510	0.7878	
		Before-Master	----	----	0.0007	----	
BS Window Sum	1/s	Master	1		24711		
		Before	24711	23476	24712	25947	
		Before-Master	----	----	1	----	
SS Window Ratio		Master	1.0000		0.4870		
		Before	0.4870	0.4626	0.4863	0.5113	
		Before-Master	----	----	-0.0007	----	
SS Window Sum	1/s	Master	1		11039		
		Before	11039	10487	11039	11591	
		Before-Master	----	----	0	----	
LS Window Ratio		Master	1.0000		0.2967		
		Before	0.2967	0.2819	0.2995	0.3116	
		Before-Master	----	----	0.0028	----	
LS Window Sum	1/s	Master	1		1233		
		Before	1233	1172	1226	1295	
		Before-Master	----	----	-7	----	

### HDRS Density Calibration - Photo-multiplier High Voltages

Master (EEPROM):		14:12:16 01-Feb-2016		Before (Measured):		13:28:55 04-Feb-2016 Expired by 7 days	
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
BS PM High Voltage	V	Master		1000	1545	2400	
		Before		1000	1540	2400	
		Before-Master	----	-100	-5	100	
SS PM High Voltage	V	Master		1000	1668	2400	
		Before		1000	1664	2400	
		Before-Master	----	-100	-4	100	
LS PM High Voltage	V	Master		1000	1570	2400	
		Before		1000	1583	2400	
		Before-Master	----	-100	13	100	

### HDRS Density Calibration - Crystal Quality Resolutions

Master (EEPROM):		14:12:16 01-Feb-2016		Before (Measured):		13:28:55 04-Feb-2016 Expired by 7 days	
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
BS Crystal Resolution	%	Master		5.00	11.77	25.00	
		Before		5.00	11.80	25.00	
		Before-Master	----	-1.00	0.03	1.00	
SS Crystal Resolution	%	Master		5.00	9.16	20.00	
		Before		5.00	9.20	20.00	
		Before-Master	----	-1.00	0.04	1.00	
LS Crystal Resolution	%	Master		5.00	8.81	20.00	
		Before		5.00	9.03	20.00	
		Before-Master	----	-1.00	0.22	1.00	

### HDRS MCFL Calibration - MCFL Accumulations

Before (Measured):		20:44:56 08-Feb-2016 Expired by 2 days					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Main Resistivity	ohm.m	Before	3875	3565	3844	4185	
Deep Resistivity	ohm.m	Before	3830	3524	3800	4136	
Shallow Resistivity	ohm.m	Before	3830	3524	3830	4136	

### HGNS-H (HILT Gamma-Ray and Neutron Sonde, 150 degC) Calibration - Run RUN1A

Primary Equipment :			
	HILT Gamma-Ray and Neutron Sonde, 150 degC	HGNS-H	4887
Auxiliary Equipment :			
	HGNS Accelerometer, 150 degC	HACCZ-H	7079

## Calibration Parameter :

Water Temperature (Calibration Tank Water Temperature)	60.7
Housing Size (Thermal Housing Size)	3.38
JIG-BKG (Jig minus background reference)	165

## HGNS Accelerometer Calibration - Accelerometer Accumulations

Before (Measured): 16:48:39 12-Feb-2016

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
AZ Vertical Measurement	ft/s2	Before	32.2	31.5	32.0	32.8	

## HGNS Accelerometer EEPROM - Accelerometer EEPROM Read

Master (EEPROM): 00:00:00 15-Jun-2007

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Accelerometer Manufacturer		Master			QAT_160		
Accelerometer Reference Temperature	degF	Master		30.2	77.0	122.0	
Accelerometer Coefficients - 0		Master	----	----	2244.000	----	
Accelerometer Coefficients - 1		Master	----	----	26.450	----	
Accelerometer Coefficients - 2		Master	----	----	0.002	----	
Accelerometer Coefficients - 3		Master	----	----	0.000	----	
Accelerometer Coefficients - 4		Master	----	----	2.725	----	
Accelerometer Coefficients - 5		Master	----	----	0.000	----	
Accelerometer Coefficients - 6		Master	----	----	0.000	----	
Accelerometer Coefficients - 7		Master	----	----	0.000	----	
Accelerometer Coefficients - 8		Master	----	----	298.800	----	
Accelerometer Coefficients - 9		Master	----	----	1.007	----	

## HGNS Neutron Calibration - HGNS Neutron Accumulations

Master (EEPROM): 16:09:48 01-Feb-2016

Before (Measured):

13:12:11 04-Feb-2016 Expired by 7 days

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Near Zero Measurement	1/s	Master	0	5.0	28.2	40.0	
		Before	0	5.0	28.2	40.0	
		Before-Master	----	-4.2	0.0	4.2	
Far Zero Measurement	1/s	Master	0	5.0	28.2	40.0	
		Before	0	5.0	33.8	40.0	
		Before-Master	----	-4.2	5.6	4.2	
Near Plus Measurement	1/s	Master	6031.0	4700.0	5018.0	6900.0	
		Before	----	----	----	----	
		Before-Master	----	----	----	----	
Far Plus Measurement	1/s	Master	2793.0	1900.0	2143.0	2900.0	
		Before	----	----	----	----	
		Before-Master	----	----	----	----	
Near Corrected Plus Measurement	1/s	Master		4700.0	5061.0	6900.0	
		Before	----	----	----	----	
		Before-Master	----	----	----	----	
Far Corrected Plus Measurement	1/s	Master		1900.0	2162.0	2900.0	
		Before	----	----	----	----	
		Before-Master	----	----	----	----	

## HGNS Gamma-Ray Calibration - Gamma-Ray Accumulations

Before (Measured): 14:05:42 04-Feb-2016 Expired by 6 days

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
RGR Zero Measurement	gAPI	Before	30.0	0	86.6	120.0	
RGR Plus Measurement	gAPI	Before	185.4	157.1	175.0	206.3	
GR Calibration Gain		Before	0.89	0.80	0.94	1.05	

## EDTC-B (Enhanced Digital Telemetry Cartridge - Version B) Calibration - Run RUN1A

Primary Equipment :

EDTC-B

EDTC-B

8001

Calibration Parameter :

Plus Reference (Jig minus background reference)

165

**EDTC-B Accelerometer Calibration - EDTC-B Accelerometer Calibration**

Before (Measured): 16:39:54 12-Feb-2016

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
AZ Vertical Measurement	ft/s2	Before	32.19	31.53	31.95	32.84	

**EDTC-B Memory Data - EDTC-B Memory Data**

Master (EEPROM): 21:50:51 12-Feb-2016

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Initial PMT HV	V	Master			1549.000		
Accelerometer Serial Number		Master			40		
Accelerometer Coefficients - 0		Master	----	----	2.945	----	
Accelerometer Coefficients - 1		Master	----	----	0.000	----	
Accelerometer Coefficients - 2		Master	----	----	0.000	----	
Accelerometer Coefficients - 3		Master	----	----	0.000	----	
Accelerometer Coefficients - 4		Master	----	----	0.000	----	
Accelerometer Coefficients - 5		Master	----	----	0.000	----	
Accelerometer Coefficients - 6		Master	----	----	0.000	----	
Accelerometer Coefficients - 7		Master	----	----	-0.005	----	
Accelerometer Coefficients - 8		Master	----	----	0.000	----	
Accelerometer Coefficients - 9		Master	----	----	0.000	----	
Accelerometer Coefficients - 10		Master	----	----	0.000	----	
Accelerometer Coefficients - 11		Master	----	----	0.000	----	
Gamma-Ray Detector Serial Number		Master			77244		

**EDTC-B Gamma-Ray Calibration - Gamma Ray Coefficients**

Before (Measured): 13:56:30 04-Feb-2016

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
Gamma Ray Gain		Before	1.000	0.900	0.978	1.100	

**EDTC-B Gamma-Ray Calibration - Gamma Ray Accumulations**

Before (Measured): 13:56:30 04-Feb-2016

Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	
RGR Zero Measurement	gAPI	Before		0	48.731	120.000	
RGR Plus Measurement	gAPI	Before	165.000	150.000	168.739	180.000	

Well: CURRY 8H  
Field: FORT BEELER  
County: MARSHALL  
State: WEST VIRGINIA

PLATFORM EXPRESS  
LITHO-DENSITY / COMPENSATED NEUTRON  
GAMMA RAY / CALIPER